

# SK world

## Dogs - Article Passport

### Product characteristics

Applications	Upholstery
Composition faceside	85% PES 15%PU
Statistic Code	-
Dyeing method	Piecedyed
Available colours	24
Minimum workable width	140 CM
Roll length	40 M
GSM	450GS/M
Backing/Finishing	Waterproof

### Colors



### Durability specifications

Test	Test Specification	Unit	Testresult	
			WARP	WEFT
Abrasion Resistance	ISO 12947-2:1998	Martindale	100000	
Colour Fastness To Water	ISO 105-X12	Grade	4-5	
Colour Fastness To Light	UNE 40187/BS 1006-B02	Grade	6	
Pilling	ISO 12945-1	Grade	5	

### Processing specifications

Test	Test Specification	Unit	Testresult	
			WARP	WEFT
Seam Slippage	ISO 13937-1:2000	mm	0	1
Tearing Strength	ISO 13934-2:2014	N	60	60
Tensile Strength	ISO 105-X12	N	800	800

### Cleaning specifications and Instructions

Test	Test Specification	Unit	Testresult	
			WARP	WEFT

#### Instructions



Wash at or below 30°



Iron, low temp.



Do not dry clean



Do not tumble dry



Do not bleach

SK world

Poligono Industrial C, Parcela B, Nave 9  
Prolongación C/Braçal del Roncador  
46800-Xàtiva-Valencia  
España  
+34 96 228 40 17

